

Specifications

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY 13.2 oz./SY	612 G/LM 442 G/SM
	Fabric Weight	2.5 oz./LY	85 G/LM
	Vinyl Weight	17.5 oz./LY	520 G/LM
	Fabric Type	Poly-Cotton Osnaburg	
	Material Width	53/54"	134/137 cm

Federal Specifications: Len-Tex Clean Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings. This product has been accepted for use by the City of New York Dept. of Buildings under MEA-381-93M.

Fire Hazard Classification Results: **ASTM E-84 Tunnel Test:** Class A, Flame Spread: 15; Smoke Developed: 10
PASS rating as tested under N FPA 286 (Corner burn test)
CAN/ULC 5102-10 Fire Test: Class A, Flame Spread: 15; Smoke Developed: 75
EN 13501-1 Fire Classification: B-s2, dO

Performance Features: Len-Tex Wallcoverings use **Clean Vinyl Technology™**

- » Phthalate-free
- » Alumina trihydrate fire retardant (antimony-free)
- » **Ultra-Fresh®** antimicrobial (non-arsenate)
- » No heavy metals or formaldehyde
- Printed exclusively with water-based, low VOC **AQUA CLEAR™** inks
- Roller applied **AQUA-CLEAR 3.0™** top finish for improved stain resistance
- Microventing for permeability is available on a custom order basis
- Advanced Warning Effect (ionization-type smoke detector)
- Five-year warranty against materials defects – Consult your distributor for details

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350
- Listed on state of California CHPS – Collaborative for High Performing Schools
- SCS Indoor Advantage™ Gold certified
- NSF/ANSI 342 certified for sustainability
- CA Prop 65 compliant
- Published Health Product Declaration (HPD) – Contributes to LEED Credits

Permeability, Moisture and Mold: Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. To reduce the risk of fungal growth, Len-Tex recommends that all wallcovering(s) be micro-vented when installed in Humid and Fringe Zone 1 climates. See full details on micro-venting at our website, www.lentexcorp.com.

Clean Vinyl Technology™ is a proprietary vinyl formulation of Len-Tex Corporation
AQUA-CLEAR 3.0™ is a proprietary top finish of Len-Tex Corporation
Ultra-Fresh® is a registered trademark of Thomson Research Associates Inc.

